

CosyFloor®

MLCP Pre-Insulated plumbing pipe for Hot, Cold and Heating services

Pre-Insulated WRAS Approved MLCP With a 6.5mm Insulation Wall

The **CosyFloor** pre-Insulated CosyPipe Pex-AL-Pex multi-layer pipe consists of 5 layers within a 6.5mm polyethylene fire-resistant insulation, manufactured according to EN 14313.

The insulation has a fire class rating of BL-S2-D0 (Class E) as per British Standard EN13501-1.

The Pre-Insulated CosyPipe offers a pre-assembled solution that combines high performance insulation with ease of installation, resulting in time & cost savings. Works in conjunction with our range of CosyPress fittings.

The **CosyFloor** Pre-Insulated CosyPipe Pex-AL-Pex multi-layer pipe has the following features:

- WRAS Approved
- Supplied in 6.5mm Insulation – Heat conductivity = 0,040 W/m*k.
- Fire resistance – Class E to BS EN13501-1
- Highly Flexible yet form stable
- Fire Resistant
- Pre-Insulated & Continuous Vapour Barrier



Sizes:

Available in 4 different sizes with either a Red or Blue insulation wall

- 16mm – 100m Coils
- 20mm – 50m Coils
- 25mm – 50m Coils
- 32mm – 25m Coils

Performance Data :

- Hot Water Operating Conditions – maximum operating temperature 70°C at 10 Bar
- Cold Water Operating Conditions – Cold Water Services >20°C with a maximum pressure operating pressure of 10 Bar
- Heating Operating Conditions – 10 Bar where the water temperature does not continuously exceed 80°C

Benefits:



Fast Installation



No further insulation or labour



Meets fire requirements for most building types



Perfect for joint-free plumbing

CosyFloor MLCP With a 6.5mm Insulation Wall Pipes are exclusively available at UFH Supplies Ltd Trading as CosyFloor
01455 247 782 - sales@cosy-floor.co.uk - www.cosyfloor.co.uk

CosyFloor